



FEATURES

Used for cutting window strips of PVC / Vinyl profiles at an angle of 45°.

- Pneumatic cutting
- Automatic returning to process starting point
- Conveyor system with measuring equipment
- Cutting and conveying speed adjustment

Standard Equipment

- Ø 4" saw blade (2 pcs)
- Ø 8" saw blade (2 pcs)
- Strip mold
- Conveyor

Optional Equipment

- Special mold
- Single-phase system

	00							$ \begin{pmatrix} \phi D & S & S \\ \hline \phi D & S & S \\ \phi d & S & S \\ \end{pmatrix} $ $ \begin{pmatrix} \phi D & S & S \\ \hline & & & & & & \\ \phi d & & & & & \\ \end{pmatrix} $ $ \begin{pmatrix} \phi D & S & S \\ \hline & & & & & \\ \phi d & & & & & \\ \end{pmatrix} $ $ \begin{pmatrix} \phi Z & S & S \\ \hline & & & & & \\ \phi d & & & & & \\ \end{pmatrix} $ $ \begin{pmatrix} \phi Z & S & S \\ \hline & & & & & \\ \phi d & & & & & \\ \end{pmatrix} $ $ \begin{pmatrix} \phi Z & S & S \\ \hline & & & & \\ \phi G & & & & \\ \end{pmatrix} $					8933						
HP kw		3∼ Hz	I (220V)	HP kw		3~Hz	I (220V)	ø D1	ø D2	ø d		S2	n	CA*	x max	y max	Air Pressure	Air Consumption	
1,5 1,1	3000 rpm	50 60	6,5 A	1,5 1,1	3000 rpm	50-60	6,5 A	7 7/8"	3 15/16"	1 1/4" 7/8"	1/16"	3/16"	3000 rpm	45°	2"	1 ³ / ₁₆ "	6-8 bar	22 Gal/min	41" x 100" x 44" 315 lbs

*CA: Cutting Angles

The product data, descriptions and illustrations are shown for advertising purpose in this document and Oz Machine, reserves the right to make modifications or improvements on data, descriptions and illustrations on this document without prior notice.





